

eliteCLEAR

TRANSFORM YOUR POOL EXPERIENCE WITH IMPROVED WATER QUALITY

The Madimack EliteCLEAR pool media filter is a cornerstone of pristine pool water. Built with non-corrosive, extra-thick fiberglass filament winding and reinforced with polyester resin, the EliteCLEAR provides robust protection against wear while preventing the accumulation of harmful particles that can damage pumps, heaters, and other equipment. With Madimack EliteCLEAR, you're choosing lasting durability and performance, for crystal-clear water and greater peace of mind season after season.



Improved Water Health



EliteCLEAR contributes to a healthier pool environment. By capturing impurities, it protects other pool equipment from wear and tear, extending their lifespan.



Effortless Maintenance

The simple backwashing process and user-friendly controls make routine upkeep a breeze, allowing you to spend more time enjoying your pool.



Universal Compatibility

Designed to accommodate a variety of pool sizes and types, this versatile filter is suitable for most residential pools.



Optimised Energy Efficiency

The filter's low resistance design minimises energy consumption, resulting in lower utility bills without compromising filtration effectiveness.



Superior Durability

Engineered with a corrosion-resistant tank and UV-resistant coating, this filter is built to withstand the elements and provide long-lasting performance.

madimack





TECHNICAL PARAMETERS

Model	Filter Dia. (mm in)	Height (mm in)	Pipe Size (mm in)	Filter Area (m ² sq ft)	Design Flow (m ³ /h l/m)	Media Weight (kg lbs)
EliteCLEAR 26	635 26	970 38	40 1.5	0.32 3.44	16 267	160 353
EliteCLEAR 28	710 28	1,040 50	40 1.5	0.40 4.3	20 333	220 485

CONTROL VALVE MAIN FUNCTIONS

Filter	Backwash	Rinse
For normal filtering and routine vacuum cleaning.	For cleaning filter when pressure gauge rises to 0.7kg/cm above start up pressure. Stop pump and turn valve to BACKWASH . Start pump until water in sight glass is clear. Approximately 2 minutes or less depending on dirt load. Proceed to rinse.	Stop pump and turn valve to RINSE . Start pump for 30 seconds. Stop pump and turn valve to FILTER for normal operating.

To get the best results from the filtration system, please read the owner manual carefully.

Use Madimack's premium **EcoBLEND** glass media in your filter.

